

AQUA
SPHERE

Lighting



Catalogue
2022



LED solutions:

PAR56 projectors, PAR56 lamps and Flat projectors

AQUA
SPHERE

PAR56 projectors



DESCRIPTION

PAR56 underwater lamp, improves energy efficiency compared to the traditional 300 W halogen PAR56 lamps. It must always be installed completely submerged. The lamps PAR56 are directly retrofittable with halogen 300 W lamps/projectors.

Lifespan of 25000 h.

The RGB lamp is controlled by a remote control with a 2 m range and can control 2 lamps. The White lamp cannot be controlled with a remote control.

To correctly light a pool it is advisable to install a light from this range every 15 m² of water surface.

Note: recommended for lighter color pools and for white light projectors. Overdimension the ratio of projectors per m² for RGB colors and pools in darker colors.

Projectors PAR56 needs a niche to complete the installation. Projector Flat to wall installations is delivered with the accessory to install in concrete and polyester pools. To complete the installation in panel pools needs spare part kit 24765-0500.

TECHNICAL FEATURES

PAR56 projectors

Image	Light color	Embellisher	Code	Consumption	Luminous flux	
	White	E A G	White	74940	11.5W (18VA)	1300 lm
			Beige	74940CL090		
			Light grey	74940CL129		
			Anthracite grey	74940CL144		
	RGB	G A G	White	71742	15 W (23 VA)	900 lm
			Beige	71742CL090		
			Light grey	71742CL129		
			Anthracite grey	71742CL144		
			White	75829		
			Beige	75829CL090		
			Light grey	75829CL129		
Anthracite grey	75829CL144					
	-	-	-	75828	-	-

Must be connected to a 12VAC safety transformer. 2.5 m cable. IPX8 protection.

TECHNICAL FEATURES

PAR56 lamps

Image	Light color	Code	Consumption	Luminous flux
	White	E A G	74939	11.5W (18VA)
	RGB	G A G	71740	15 W (23 VA)
	-	-	75828	-

Must be connected to a 12VAC safety transformer. IPX8 protection.

Flat projectors

Image	Light color	Code	Consumption	Luminous flux
	White	E A G	74941	11.5W (18VA)
	RGB	G A G	71744	15 W (23 VA)
	-	-	75828	-

Must be connected to a 12VAC safety transformer. 2.5 m cable. IPX8 protection.

AQUA
SPHERE